

LEDsolution 2.5mm Die-Cast Indoor SMD LED Panel



SHENZHEN LEDSOLUTION TECHNOLOGY CO.,LTD

Update 2017-1-1

Parameter	Unit	Value
Pitch	mm	2.5
Brightness	nits	800
Color temperature	deg. K	6,500
Viewing angle - Horizontal (50% brightness)	deg.	140(-70 ~ +70)
Viewing angle - Vertical (50% brightness)	deg.	140(-70 ~ +70)
Panel weight	kg	7
Panel width	mm	480
Panel height	mm	480
Panel depth	mm	89.5
Panel area	sq. m.	0.2304
Panel material		Aluminum alloy
Panel service access		Front & Back
Operating temperature range	deg. C	-20 to +60
Humidity operating	RH	10% ~ 60%
Pixel type and configuration	R/G/B	3-in-1 SMD
Resolution per panel		192x192
Dot per panel		36,864
Dot per sq. meter		160,000
LED per sq. meter		160,000
Recommended minimum viewing distance	m	2
Recommended best viewing distance	m	2-50
Colors		281 Trillion
Grey scale (linear)	Levels	65,536
Brightness control	Levels	256
Contrast ratio		2,000:1
Processing depth	bit	16
Video frame rate	Hertz	60
Display refresh rate	Hertz	1,200
Input voltage (nominal)	VAC	110 to 240
Input power frequency	Hertz	50 to 60
Input power (max)	Watts / panel.	200
Input power (typical)	Watts / panel.	80
Lifetime (50% brightness)	Hours	≥100,000
Red wavelength (dominant)	nm	620~625
Green wavelength (dominant)	nm	520~525
Blue wavelength (dominant)	nm	470~475
Multimedia data format		DVI,MPG,AVI,WMV,RM etc.
Data interconnection		UTP Cat 5
Mounting system		Fixed & Rental

*LEDSolution reserves the right to change any specifications without notice.