

LEDSOLUTION 3.076mm Permanent Indoor SMD LED Panel

LEDSOLUTION®



www.iledsolution.com

SHENZHEN LEDSOLUTION TECHNOLOGY CO.,LTD

Update 2013-1-1

Parameter	Value
Model	LS-I-P3.076-0.96mx0.96m
Application	Indoor
Pitch	3.076mm
Pixel density	105625dot/sq.m
LED density	105625dot/sq.m
Brightness	1000nit
Color temperature	6500deg. K
Viewing angle - Horizontal	140(-70 ~ +70) deg.
Viewing angle - Vertical	140(-70 ~ +70)deg.
Module size(W*H)	320*160mm
Module resolution(W*H)	104*52pixel
Module Qty(W*H)	3*6=18pcs
Cabinet size(W*H)	960*960mm
Cabinet depth	100mm
Cabinet sq. meter	0.9216sq.m
Cabinet resolution(W*H)	312*312pixel
Cabinet weight	30kg /sq.m
Cabinet mode	Fixed installation
Service access	Back service or front service
Ingress protection (front/rear)	IP23
Operating temperature range	-30 to +60 deg. C
Humidity operating	10% ~ 90% RH
Pixel type and configuration	3in1 SMD
Recommended minimum viewing distance	2.3m
Recommended best viewing distance	2~100m
Colors	281 Trillion
Grey scale (linear)	65536 levels per color
Brightness control	100Levels
Contrast ratio	3000:1
Processing depth	16bit
Video frame rate	60Hertz
Display refresh rate	1920Hertz
Input voltage (nominal)	110 or 220VAC
Input power frequency	50 to 60 Hertz
Input power (max)	600 Watts/Ssq.meter
Input power (typical)	240 Watts/Ssq.meter
Lifetime (50% brightness)	≥100000
Red wavelength (dominant)	620~625
Green wavelength (dominant)	525~530
Blue wavelength (dominant)	470~475

Multimedia data format	DVI,MPG,AVI,WMV,RM etc.
Data interconnection	UTP Cat 5/Optical Fiber
Mounting system	Fixed with 4pcs M10 bolts
Controller	NOVA

*LEDSOLUTION reserves the right to change any specifications without notice.