

LEDsolution 6mm Rental Indoor SMD LED Panel



SHENZHEN LEDSOLUTION TECHNOLOGY CO.,LTD

Update 2011-1-1

Parameter	Unit	Value
Pitch	mm	6
Brightness	nits	2,000
Color temperature	deg. K	6,500
Viewing angle - Horizontal (50% brightness)	deg.	140(-70 ~ +70)
Viewing angle - Vertical (50% brightness)	deg.	140(-70 ~ +70)
Panel weight	kg	34
Panel width	mm	768
Panel height	mm	768
Panel depth	mm	150
Panel area	sq. m.	0.59
Panel material		Epoxy paint coated Aluminum
Panel Mode		Quick Assembly Cabinet
Operating temperature range	deg. C	-30 to +60
Humidity operating	RH	10% ~ 90%
Pixel type and configuration	R/G/B	3in1 SMD
Resolution per panel		128x128
Dot per panel		16,384
Dot per sq. meter		27,778
LED per sq. meter		27,778
Recommended minimum viewing distance	m	6
Recommended best viewing distance	m	8~20
Colors		281 trillion
Grey scale (linear)	Levels	65,536 levels per color
Brightness control	Levels	100
Contrast ratio		1,000:1
Processing depth	bit	16
Video frame rate	Hertz	60
Display refresh rate	Hertz	600
Input voltage (nominal)	VAC	110 to 240
Input power frequency	Hertz	50 to 60
Input power (max)	Watts /Cabinet	600
Input power (typical)	Watts /Cabinet	240
Lifetime (50% brightness)	Hours	≥100,000
Red wavelength (dominant)	nm	620~625
Green wavelength (dominant)	nm	520~525
Blue wavelength (dominant)	nm	470~475
Multimedia data format		DVI,MPG,AVI,WMV,RM etc.
Data interconnection		UTP Cat 5/Optical Fiber
Mounting system		Fixed with 4pcs M10 bolts

*LEDSolution reserves the right to change any specifications without notice.