

LEDSolution 16mm Permanent Outdoor Oval LED Panel

LEDSOLUTION



www.ledsolution-cor.com

SHENZHEN LEDSOLUTION TECHNOLOGY CO.,LTD

Update 2011-1-1

Parameter	Unit	Value
Pitch	mm	16
Brightness	nits	6,000
Color temperature	deg. K	6,500
Viewing angle - Horizontal (50% brightness)	deg.	130 (+65/-65)
Viewing angle - Vertical (50% brightness)	deg.	60(+30/-30)
Panel weight	kg	54
Panel width	mm	1,280
Panel height	mm	768
Panel depth	mm	170
Panel area	sq. m.	0.983
Panel material		Epoxy paint coated Cold rolled steel
Ingress protection (front/rear)	IP	IP65/IP65
Operating temperature range	deg. C	-30 to +60
Humidity operating	RH	10% ~ 90%
Pixel type and configuration	R/G/B	1,1,1
Resolution per panel		80x48
Dot per panel		3,840
Dot per sq. meter		3,906
LED per sq. meter		11,718
Recommended minimum viewing distance	m	12
Recommended best viewing distance	m	16~48
Colors		281 Trillion
Grey scale (linear)	Levels	65,536 levels per color
Brightness control	Levels	100
Contrast ratio		1,000:1
Processing depth	bit	16
Video frame rate	Hertz	60
Display refresh rate	Hertz	180~3,000
Input voltage (nominal)	VAC	110 to 240
Input power frequency	Hertz	50 to 60
Input power (max)	Watts /Cabinet	1,200
Input power (typical)	Watts /Cabinet	480
Lifetime (50% brightness)	Hours	≥100,000
Red wavelength (dominant)	nm	620~625
Green wavelength (dominant)	nm	520~525
Blue wavelength (dominant)	nm	470~475
Multimedia data format		DVI,MPG,AVI,WMV,RM etc.
Data interconnection		UTP Cat 5
Mounting system		Fixed with 4pcs M10 bolts

*LEDSolution reserves the right to change any specifications without notice.