

LEDsolution 6.25mm Slim Indoor SMD LED Panel



SHENZHEN LEDSOLUTION TECHNOLOGY CO.,LTD

Update 2012-1-1

Cabinet Pictures:**Features:**

1. Light weight only 9.2kg/panel;
2. Low noise design;
3. Slim type with thickness only 65mm;
4. Easy assembly without any tools, agile installation for hanging or ground installation;
5. ± 15 flexible arc installation to realize inner curve or outer curve.

Parameter	Unit	Value
Pitch	mm	6.25
Brightness	nits	2,000
Color temperature	deg. K	6,500
Viewing angle - Horizontal (50% brightness)	deg.	140(-70 ~ +70)
Viewing angle - Vertical (50% brightness)	deg.	140(-70 ~ +70)
Panel weight	kg	9.2
Panel width	mm	500
Panel height	mm	1,000
Panel depth	mm	65
Panel area	sq. m.	0.5
Panel material		Epoxy paint coated Aluminum
Panel Mode		Slim rental
Operating temperature range	deg. C	-30 to +60
Humidity operating	RH	10% ~ 90%
Pixel type and configuration	R/G/B	3in1 SMD
Resolution per panel		80x160
Dot per panel		12,800
Dot per sq. meter		25,600
LED per sq. meter		25,600
Recommended minimum viewing distance	m	5
Recommended best viewing distance	m	7~21
Colors		281 Trillion
Grey scale (linear)	Levels	65,536 levels per color
Brightness control	Levels	100
Contrast ratio		1,000:1
Processing depth	bit	16
Video frame rate	Hertz	60
Display refresh rate	Hertz	180~3,000
Input voltage (nominal)	VAC	110 to 240
Input power frequency	Hertz	50 to 60
Input power (max)	Watts / panel.	400
Input power (typical)	Watts / panel.	160
Lifetime (50% brightness)	Hours	≥100,000
Red wavelength (dominant)	nm	620~625
Green wavelength (dominant)	nm	520~525
Blue wavelength (dominant)	nm	470~475
Multimedia data format		DVI,MPG,AVI,WMV,RM etc.
Data interconnection		UTP Cat 5/Optical Fiber
Mounting system		Hanging / Fixed

*LEDSolution reserves the right to change any specifications without notice.